## NSN 5985-00-421-8053

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-421-8053

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.751 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.338 inches
Overall Height:
0.695 inches
Overall Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Coaxial Connector Series Designation:
Osm
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 13.275 gigahertz and 13.375 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Adjustment Device Type And Quantity:
1 motor
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Special Features:
Fourth mtg hole offset from other three mtg holes
Terminal Type And Quantity:
3 connector, coaxial, male and 2 tab, solder lug
Fsc Application Data:
Test set, electronic systems
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-00-421-8053

Variable Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A223a0