

View Online at <https://aerobasegroup.com/nsn/5985-00-429-2037>

**Application Design:**

Audio

**Body Style:**

Cylindrical w/side and rear terminals

**Overall Length:**

1.297 inches

**Body Diameter:**

Between 0.495 inches and 0.505 inches

**Shaft Diameter:**

Between 0.124 inches and 0.126 inches

**Bushing Length:**

Between 0.370 inches and 0.380 inches

**Shaft Length:**

0.500 inches

**Body Length:**

0.547 inches

**Overall Diameter:**

Between 0.745 inches and 0.755 inches

**Schematic Diagram Designator:**

Bridged "t"

**Operating Temperature Range:**

-55.0/+120.0 degrees celsius

**Power Rating:**

250.0 milliwatts average

**Mounting Facility Screw Thread Series Designator:**

Unef

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

0.6

**Overall Attenuation Range In Decibels:**

+0.0/+20.0

**Attenuation Variation Method:**

Continuous

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Overall Attenuation Accuracy In Decibels:**

-1.00/+1.00

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

1 shaft

**Shaft Type:**

Round, slotted

**Mounting Facility Screw Thread Diameter:**

0.250 inches

**Impedance Rating In Ohms:**

135.0 input-output

**Test Data Document:**

13499-383-0273 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 tab, solder lug

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A223a0