NSN 5985-00-431-0354

Fixed Attenuator - Page 1 of 2

Application Design:



View Online at https://aerobasegroup.com/nsn/5985-00-431-0354

Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
1.937 inches
Overall Diameter:
0.536 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sm
Power Rating:
1.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
1.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+1.0 gigahertz and +1.0/+2.0 gigahertz
Attenuation Accuracy In Decibels:
-0.10/+0.10
Connection Type Per Function:
Female output and male input
Female output and male input Mounting Method:
·
Mounting Method:
Mounting Method: Connector
Mounting Method: Connector Terminal Type And Quantity:
Mounting Method: Connector Terminal Type And Quantity: 2 connector
Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz
Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz Shelf Life:

NSN 5985-00-431-0354

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000