# NSN 5985-00-431-6122

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-431-6122

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

#### Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

#### Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

#### Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

# Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

# Flange Depth:

0.423 inches second flange and 0.453 inches second flange

#### Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

# **Voltage Standing Wave Ratio:**

1.08

# **Maximum Operating Pressure:**

20.0 pounds per square inch gage

#### **Waveguide Outside Width:**

Between 0.996 inches and 1.004 inches

#### **Thread Size:**

0.164 inches first flange all connection facilities

# Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

#### **Waveguide Inside Height:**

Between 0.396 inches and 0.404 inches

# **Waveguide Outside Height:**

Between 0.496 inches and 0.504 inches

# **Waveguide Longer Offset Distance:**

Between 2.219 inches and 2.281 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

# **NSN 5985-00-431-6122** Waveguide Assembly - Page 2 of 2



Flange Style:
Cover type second flange
Waveguide Offset Distance:
Between 1.719 inches and 1.781 inches
Flexibility:
Flexible single tubing segment
Material:
Plastic single tubing jacket
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Silver single tubing segment inside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0