## NSN 5985-00-432-7653

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-432-7653

Body Style:
Cylindrical w/side terminals
Overall Length:
4.062 inches
Bolt Circle Diameter:
1.500 inches
Overall Width:
3.110 inches
First Flat Length:
0.312 inches
Flat Height:
0.218 inches
Body Diameter:
2.781 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.812 inches
Body Length:
3.250 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+45.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
45
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 threaded hole
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
2 shaft
Mounting Facility Pattern:
Four position circular
Shaft Type:

Round, flatted

## NSN 5985-00-432-7653

Variable Attenuator - Page 2 of 2

Fiig: A223a0



## Mounting Facility Screw Thread Diameter: 0.164 inches Special Features: Two unit tandem type, cylindrical w/side terminals, 4.062 in. Lg Terminal Type And Quantity: 8 tab, solder lug Shelf Life: N/a Unit Of Measure: -- Demilitarization: No