

View Online at <https://aerobasegroup.com/nsn/5985-00-433-6758>

Body Style:

Irregular

Overall Length:

2.070 inches

Overall Height:

2.970 inches

Overall Width:

1.090 inches

Frequency Rating:

0.0 gigahertz and 12.4 gigahertz single frequency operating0.0 gigahertz and 12.4 gigahertz single frequency voltage standing wave ratio0.0 gigahertz and 12.4 gigahertz single frequency insertion loss reference0.0 gigahertz and 12.4 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.203 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

0.885 inches single mounting facility pattern

Operating Temperature Range:

-54.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.50 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.5 dc

Actuator Voltage In Volts:

Between 18.0 and 30.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Aluminum body

Surface Treatment:

Paint body outside surfaces

Terminal Type And Quantity:

3 receptacle, coaxial and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0