

View Online at <https://aerobasegroup.com/nsn/5985-00-433-8513>

Thread Class:

2b mounting facility hole

Overall Length:

Between 2.718 inches and 2.781 inches

Overall Height:

Between 2.094 inches and 2.156 inches

Frequency Rating:

5.4 gigahertz and 5.9 gigahertz single frequency insertion loss reference

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.273 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.273 inches single mounting facility pattern

Operating Temperature Range:

+0.0/+55.0 degrees celsius

End Application:

Missile guidance and tracking set an/spg-55b

Insertion Loss In Decibels:

1.50 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

2.0 watts peak single

Minimum Crosstalk Rating In Decibels:

25.0 single

Actuator Operating Method:

Solid state

Switching Time:

0.01 microseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

2

Throw Quantity:

2

Coupling Position Quantity:

6

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.086 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Aluminum body

Surface Treatment:

Chromate body outside surfaces

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

6 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0