NSN 5985-00-434-2235

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-434-2235

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
9.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches
Overall Height:
3.380 inches
Overall Width:
5.000 inches
Mounting Slot Width:
0.187 inches
Mounting Slot Length:
0.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.000 inches
Operating Tempurature Range:
+0.0/+55.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.30 and 1.35 and 1.45 and 1.50
Coaxial Connector Series Designation:
N
Power Rating:
1.0 watts average and 500.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.2
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
16
Attenuation Per Step In Decibels:
1.0 and 10.0
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Overall Attenuation Accuracy In Decibels:
+0.00/+0.15
Segment Attenuation Range In Decibels:
+1.00/+9.00 and +10.00/+19.00 and +20.00/+29.00 and +30.00/+39.00 and +40.00/+49.00 and +50.00/+59.00

NSN 5985-00-434-2235

Variable Attenuator - Page 2 of 2



Caamant	Attenuation	A	Iس	Decibales
Seament	Allenuation	Accuracy	ш	Decibeis.

-0.40/+0.40 and -1.00/+1.00 and -1.20/+1.20 and -1.40/+1.40 and -1.50/+1.50 and -1.70/+1.70

Adjustment Device Type And Quantity:

2 knob

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Special Features:

Attenuation accuracy measured at 1.0, 2.0, 4.0, 8.0, and 12.4 gigahertz

Test Data Document:

12217-1291029 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0