## NSN 5985-00-434-2281

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-434-2281 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 3.656 inches **Overall Height:** 3.547 inches **Overall Width:** 1.000 inches **Voltage Standing Wave Ratio:** 1.30 **Coaxial Connector Series Designation:** Sma **Power Rating:** 10.0 watts average and 3.0 kilowatts peak **Mounting Facility Screw Thread Series Designator:** Unc **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 1.0 **Overall Attenuation Range In Decibels:** +0.0/+45.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 3 threaded hole Frequency Range: Between 12.400 gigahertz and 18.000 gigahertz **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 slotted screw **Mounting Facility Screw Thread Diameter:** 0.138 inches **Terminal Type And Quantity:** 2 connector, coaxial, female Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5985-00-434-2281

Variable Attenuator - Page 2 of 2



Fiig:

A223a0