NSN 5985-00-434-4321

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-434-4321

Application Design: Transmission line **Body Material:** Aluminum alloy **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Anodized **Overall Length:** 3.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.470 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches **Overall Height:** Between 1.500 inches and 1.620 inches **Overall Width:** 1.750 inches **Mounting Hole/stud Quantity: Unthreaded Mounting Hole Diameter:** Between 0.191 inches and 0.196 inches **Operating Tempurature Range:** -54.0/+71.0 degrees celsius **Voltage Standing Wave Ratio:** 1.20 **Input Impedance Rating In Ohms: Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 5.0 watts average and 1.0 kilowatts peak Rf Signal Attenuation In Decibels: **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz **Connection Type Per Function:** Female output and female input and male output and male input

Mounting Method:

Flange w/mounting hole

NSN 5985-00-434-4321

Fixed Attenuator - Page 2 of 2



Termina	I Type	And C	Quantity:
ı Cı illili	IIVDE	Allu V	zuannıv.

2 connector

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000