## NSN 5985-00-434-4322

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-434-4322

Application Design:
Transmission line
Body Material:
Aluminum alloy
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Body Surface Treatment:
Anodized
Overall Length:
5.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.190 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.250 inches
Overall Height:
1.620 inches
Overall Width:
1.750 inches
Mounting Hole/stud Quantity:
4
Unthreaded Mounting Hole Diameter:
Between 0.191 inches and 0.196 inches
Operating Tempurature Range:
-54.0/+71.0 degrees celsius
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
26.0 watts average and 4.0 kilowatts peak
Rf Signal Attenuation In Decibels:
30.0
Connection Type Per Function:
Female output and female input and male output and male input
Mounting Method:
Flange w/mounting hole
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 1.100 gigahertz

## NSN 5985-00-434-4322

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

