NSN 5985-00-436-2032



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-436-2032 **Application Design:** Waveguide **Body Style:** Irregular **Overall Length:** 11.156 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.500 inches **Overall Height:** 6.375 inches **Overall Width:** 7.000 inches Scale Linearity: Linear **Unthreaded Mounting Hole Diameter:** 0.188 inches **Power Rating:** 10.0 watts peak **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.5 **Overall Attenuation Range In Decibels:** +0.0/+60.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 7.050 gigahertz and 10.000 gigahertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Adjustment Device Type And Quantity:** 1 knob **Terminal Type And Quantity:** 2 flange Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5985-00-436-2032

Variable Attenuator - Page 2 of 2



Fiig:

A223a0