NSN 5985-00-436-2032

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-436-2032

View Online at https://aerobasegroup.com/nsn/5985-00-436-2032
Application Design:
Waveguide
Body Style:
Irregular
Overall Length:
11.156 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.500 inches
Overall Height:
6.375 inches
Overall Width:
7.000 inches
Scale Linearity:
Linear
Unthreaded Mounting Hole Diameter:
0.188 inches
Power Rating:
10.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 7.050 gigahertz and 10.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Adjustment Device Type And Quantity:
1 knob
Terminal Type And Quantity:
2 flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 5985-00-436-2032

Variable Attenuator - Page 2 of 2

Fiig: A223a0

