

View Online at <https://aerobasegroup.com/nsn/5985-00-437-6896>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 third bend h-plane

End Application:

Transmitting set, aircraft approach control an/trn-28

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches second flange and 0.707 inches second flange

Flange Inside Height:

0.394 inches second flange and 0.396 inches second flange

Flange Outside Width:

1.298 inches second flange and 1.328 inches second flange

Flange Outside Height:

1.298 inches second flange and 1.328 inches second flange

Flange Inside Diameter:

0.994 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Second Leg Length:

10.937 inches

Waveguide Third Leg Length:

2.390 inches

Waveguide Fourth Leg Length:

1.125 inches

Flexibility:

Rigid fifth tubing segment

Material:

Copper alloy first tubing segment

Surface Treatment:

Any acceptable all flange inside surfaces

Style Designator:

Three bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A073a0