

View Online at <https://aerobasegroup.com/nsn/5985-00-438-3275>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

Flange Outside Width:

1.609 inches second flange and 1.641 inches second flange

Flange Outside Height:

1.609 inches second flange and 1.641 inches second flange

Flange Depth:

0.438 inches second flange

Flange Connecting Hole Diameter:

0.171 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.10

Thready Qty Per Inch (tpi):

32 all flanges all connection facilities

Waveguide Outside Width:

Between 0.997 inches and 1.003 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.897 inches and 0.903 inches

Waveguide Inside Height:

Between 0.397 inches and 0.403 inches

Waveguide Outside Height:

Between 0.497 inches and 0.503 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

Between 4.496 inches and 5.540 inches

Flexibility:

Flexible all tubing segment

Material:

Rubber synthetic all tubing jacket

Surface Treatment:

Silver all tubing segment and flange all surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0