

View Online at <https://aerobasegroup.com/nsn/5985-00-438-3275>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b all flanges all connection facilities

**Thread Direction:**

Right-hand all flanges all connection facilities

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.003 inches second flange and 1.006 inches second flange

**Flange Inside Height:**

0.503 inches second flange and 0.506 inches second flange

**Flange Outside Width:**

1.609 inches second flange and 1.641 inches second flange

**Flange Outside Height:**

1.609 inches second flange and 1.641 inches second flange

**Flange Depth:**

0.438 inches second flange

**Flange Connecting Hole Diameter:**

0.171 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.15

**Insertion Loss In Decibels:**

0.10

**Thready Qty Per Inch (tpi):**

32 all flanges all connection facilities

**Waveguide Outside Width:**

Between 0.997 inches and 1.003 inches

**Thread Size:**

0.164 inches all flanges all connection facilities

**Waveguide Inside Width:**

Between 0.897 inches and 0.903 inches

**Waveguide Inside Height:**

Between 0.397 inches and 0.403 inches

**Waveguide Outside Height:**

Between 0.497 inches and 0.503 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole first flange single connection facility

**Flange Style:**

Cover type second flange

**Waveguide Length:**

Between 4.496 inches and 5.540 inches

**Flexibility:**

Flexible all tubing segment

**Material:**

Rubber synthetic all tubing jacket

**Surface Treatment:**

Silver all tubing segment and flange all surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc all flanges all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0