

View Online at <https://aerobasegroup.com/nsn/5985-00-438-3276>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a second flange second connection facility

Thread Direction:

Right-hand second flange second connection facility

Tubing Wall Construction Style:

Laminated second tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches second flange and 0.903 inches second flange

Flange Inside Height:

0.397 inches second flange and 0.403 inches second flange

Flange Outside Width:

3.000 inches first flange

Flange Outside Height:

3.000 inches first flange

Flange Depth:

0.312 inches second flange

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.10

Adapter Length:

1.245 inches

Waveguide Outside Width:

Between 0.997 inches and 1.003 inches

Thread Size:

0.164 inches second flange second connection facility

Waveguide Inside Width:

Between 0.897 inches and 0.903 inches

Waveguide Inside Height:

Between 0.397 inches and 0.403 inches

Waveguide Outside Height:

Between 0.497 inches and 0.503 inches

Flange Connecting Facility And Quantity:

4 threaded hole second flange second connection facility

Flange Style:

Cover type second flange

Material:

Copper alloy all tubing segment and flange

Style Designator:

Waveguide to waveguide

Thread Series Designator:

Unc second flange second connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0