

View Online at <https://aerobasegroup.com/nsn/5985-00-439-5691>

Thread Class:

2b mounting facility hole

Body Style:

Rectangular

Overall Length:

3.384 inches

Overall Height:

2.960 inches

Overall Width:

2.750 inches

Frequency Rating:

0.0 gigahertz and 10.0 gigahertz single frequency crosstalk reference

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.187 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.187 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.30 single

Insertion Loss In Decibels:

0.31 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female and male

Rf Power Handling Capability:

100.0 watts average single

Minimum Crosstalk Rating In Decibels:

50.0 single

Actuator Operating Method:

Manual

Switch Operation Sequence:

Breaks before makes

Pole Quantity:

1

Throw Quantity:

2

Rf Maximum Voltage Rating:

500.0 volts rms

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.112 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Metal body

Test Data Document:

81349-mil-s-3928 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0