NSN 5985-00-443-3681

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-443-3681

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Connecting Hole Diameter:

0.107 inches second flange all connection facilities and 0.112 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.20

Thready Qty Per Inch (tpi):

56 first flange all connection facilities

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.086 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

3 unthreaded hole second flange all connection facilities

Waveguide Length:

Between 0.615 inches and 0.635 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

NSN 5985-00-443-3681

Waveguide Assembly - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0