## NSN 5985-00-443-5827

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-443-5827

| Application Design:  |
|--|
| Transmission line  |
| Body Style:  |
| Coaxial type   |
| Overall Length:  |
| 4.180 inches   |
| Overall Height:  |
| 2.120 inches   |
| Overall Width:   |
| 2.060 inches   |
| Operating Tempurature Range:                               |
| +0.0/+50.0 degrees celsius                                 |
| Voltage Standing Wave Ratio:                               |
| 1.50   |
| Coaxial Connector Series Designation:                      |
| Tnc  |
| Power Rating:  |
| 4.0 watts average  |
| Mounting Facility Screw Thread Series Designator:          |
| Unc  |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.5  |
| Overall Attenuation Range In Decibels:                     |
| +0.0/+30.0   |
| Attenuation Variation Method:                              |
| Continuous   |
| Mounting Facility Type And Quantity:                       |
| 8 threaded stud  |
| Frequency Range:   |
| Between 3.000 gigahertz and 9.000 gigahertz                |
| Mounting Thread Quantity:                                  |
| 32 per inch  |
| Adjustment Device Type And Quantity:                       |
| 1 knob   |
| Mounting Facility Screw Thread Diameter:                   |
| 0.138 inches   |
| Impedance Rating In Ohms:                                  |
| 50.0 input-output  |
| Terminal Type And Quantity:                                |
| 2 connector, coaxial, female                               |
| Shelf Life:  |

N/a

## NSN 5985-00-443-5827

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0