NSN 5985-00-445-5832

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-00-445-5832

Body Material:
Aluminum alloy
Body Style:
Round, terminal/terminals in opposite surface
Terminal Material:
Metal
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
3.690 inches
Overall Diameter:
0.930 inches
Voltage Standing Wave Ratio:
1.20
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
500.0 milliwatts average
Rf Signal Attenuation In Decibels:
38.6
Voltage Standing Wave Ratio Frequency Range:
+19.0/+25.0 megahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 19.000 megahertz and 25.000 megahertz
Fsc Application Data:

Antennas, waveguies and related equip.

NSN 5985-00-445-5832

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000