NSN 5985-00-446-2664

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-446-2664

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.844 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.000 inches
Overall Height:
1.438 inches
Overall Width:
18.688 inches
Coaxial Connector Series Designation:
Bnc
Power Rating:
20.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+3.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
0.5
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 225.000 hertz and 400.000 hertz
Overall Attenuation Accuracy In Decibels:
-0.30/+0.30
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
3 pushbutton
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.112 inches

NSN 5985-00-446-2664

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, male

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0