

View Online at <https://aerobasegroup.com/nsn/5985-00-446-2756>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Depth:

0.438 inches all flanges

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.10

Waveguide Outside Width:

Between 0.997 inches and 1.003 inches

Thread Size:

0.164 inches all flanges single connection facility

Waveguide Inside Width:

Between 0.897 inches and 0.903 inches

Waveguide Inside Height:

Between 0.397 inches and 0.403 inches

Waveguide Outside Height:

Between 0.497 inches and 0.503 inches

Waveguide Longer Offset Distance:

Between 4.094 inches and 4.156 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Offset Distance:

Between 2.719 inches and 2.781 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Surface Treatment:

Silver single tubing segment inside surfaces and rhodium single tubing segment inside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc all flanges single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0