

View Online at <https://aerobasegroup.com/nsn/5985-00-447-0395>

Body Style:

Irregular

Overall Length:

3.938 inches

Overall Height:

2.149 inches

Overall Width:

2.656 inches

Frequency Rating:

0.0 gigahertz and 6.0 gigahertz single frequency operating
0.0 gigahertz and 6.0 gigahertz single frequency voltage standing wave ratio
0.0 gigahertz and 6.0 gigahertz single frequency insertion loss reference
0.0 gigahertz and 6.0 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.205 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.375 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.688 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.625 inches single mounting facility pattern

Operating Temperature Range:

-58.0/+55.0 degrees celsius

Voltage Standing Wave Ratio:

1.40 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Rf Power Handling Capability:

100.0 watts average single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

1.5 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

15.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Rf Maximum Voltage Rating:

500.0 volts peak

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Material:

Metal body

Surface Treatment:

Enamel body outside surfaces

Terminal Type And Quantity:

3 receptacle, coaxial and 1 plug, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0