Radio Frequency Transmission Line Switch - Page 1 of 2



Body Style: Rectangular Overall Length: 2.500 inches Overall Height: 1.562 inches Overall Width: 2.000 inches Frequency Rating: 2.0 megahertz and 30.0 megahertz single frequency operating2.0 megahertz and 30.0 megahertz single frequency crosstalk reference
Overall Length:2.500 inchesOverall Height:1.562 inchesOverall Width:2.000 inchesFrequency Rating:
2.500 inches Overall Height: 1.562 inches Overall Width: 2.000 inches Frequency Rating:
Overall Height: 1.562 inches Overall Width: 2.000 inches Frequency Rating:
1.562 inches Overall Width: 2.000 inches Frequency Rating:
Overall Width: 2.000 inches Frequency Rating:
2.000 inches Frequency Rating:
Frequency Rating:
2.0 megahertz and 30.0 megahertz single frequency operating 2.0 megahertz and 30.0 megahertz single frequency crosstalk reference
Switch Type:
Transfer
Longest Horizontal Distance Between Mounting Centers:
0.875 inches single mounting facility pattern
Longest Vertical Distance Between Mounting Centers:
0.875 inches single mounting facility pattern
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.05 single
Insertion Loss In Decibels:
1.20 single
Coaxial Connector Series Designation:
Bnc
Rf Power Handling Capability:
100.0 watts average single
Minimum Crosstalk Rating In Decibels:
35.0 single
Actuator Operating Method:
Relay
Actuator Voltage In Volts:
32.0
Switch Operation Sequence:
Breaks before makes
Switch Return Mechanism Type:
Fail-safe
Coupling Position Quantity:
3
Mounting Facility Type And Quantity:
4 threaded hole
Thread Size:
0.112 inches mounting facility hole



Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

2 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A158a0