

View Online at <https://aerobasegroup.com/nsn/5985-00-449-6428>

Thread Class:

2b mounting facility hole

Body Style:

Cylindrical

Overall Length:

5.175 inches

Overall Height:

4.500 inches

Frequency Rating:

2.0 megahertz and 32.0 megahertz single frequency operating

Overall Diameter:

2.750 inches

Switch Type:

Nontransfer

Operating Temperature Range:

-28.0/+65.0 degrees celsius

Voltage Standing Wave Ratio:

1.10 single

Coaxial Connector Series Designation:

C

Connector End Design:

Female

Rf Power Handling Capability:

5.0 kilowatts average single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.6 dc

Actuator Voltage In Volts:

115.0

Pole Quantity:

1

Throw Quantity:

6

Rf Maximum Voltage Rating:

2.0 kilovolts peak

Coupling Position Quantity:

7

Mounting Facility Circle Radius:

1.937 inches single mounting facility pattern

Mounting Facility Type And Quantity:

8 threaded hole

Thread Size:

0.190 inches mounting facility hole

Mounting Facility Pattern:

Eight position circular single mounting facility pattern

Special Features:

Xmtr enabling provision

Surface Treatment:

Enamel body outside surfaces

Surface Treatment Specification:

Mil-e-15090 military specification single treatment response body outside surfaces

Supplementary Features:

10000 cycle life expectancy

Thread Series Designator:

Unf mounting facility hole

Terminal Type And Quantity:

1 connector, receptacle and 7 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0

Mil-std (military Standard):

Mil-e-15090 spec.