NSN 5985-00-451-2118

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-451-2118

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange

Flange Inside Height:

1.002 inches second flange

Flange Outside Diameter:

3.625 inches second flange

Flange Depth:

0.938 inches first flange

Flange Connecting Hole Diameter:

0.199 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.06

Insertion Loss In Decibels:

0.025

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches first flange single connection facility

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

1.000 feet

NSN 5985-00-451-2118 Waveguide Assembly - Page 2 of 2



Flexibility:
Flexible single tubing segment
Material:
Copper alloy all flange
Precious Material And Location:
Flange surface silver
Precious Material:
Silver
Surface Treatment:
Silver all flange inside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unf first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0