

View Online at <https://aerobasegroup.com/nsn/5985-00-451-8263>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches first flange and 0.707 inches first flange

Flange Inside Height:

0.394 inches first flange and 0.396 inches first flange

Flange Outside Width:

1.298 inches first flange and 1.328 inches first flange

Flange Outside Height:

1.298 inches first flange and 1.328 inches first flange

Flange Inside Diameter:

0.985 inches second flange and 1.015 inches second flange

Flange Depth:

0.360 inches second flange and 0.390 inches second flange

Flange Connecting Hole Diameter:

0.144 inches first flange all connection facilities and 0.147 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Thready Qty Per Inch (tpi):

32 second flange all connection facilities

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches second flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

Flange Style:

Cover type first flange

Waveguide Center To Center Distance:

18.000 inches

Waveguide Height:

17.530 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all tubing segment and flange

Precious Material And Location:

Internal tubing segment surfaces and flange surfaces silver

Precious Material:

Silver

Surface Treatment:

Chromate zinc single tubing segment outside surfaces and enamel single tubing segment outside surfaces

Style Designator:

Double bend type

Thread Series Designator:

Unc second flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0