NSN 5985-00-451-8263

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-451-8263

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches first flange and 0.707 inches first flange

Flange Inside Height:

0.394 inches first flange and 0.396 inches first flange

Flange Outside Width:

1.298 inches first flange and 1.328 inches first flange

Flange Outside Height:

1.298 inches first flange and 1.328 inches first flange

Flange Inside Diameter:

0.985 inches second flange and 1.015 inches second flange

Flange Depth:

0.360 inches second flange and 0.390 inches second flange

Flange Connecting Hole Diameter:

0.144 inches first flange all connection facilities and 0.147 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Thready Qty Per Inch (tpi):

32 second flange all connection facilities

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches second flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

NSN 5985-00-451-8263 Waveguide Assembly - Page 2 of 2

Fiig: A073a0



Flange Connecting Facility And Quantity:
4 unthreaded hole first flange all connection facilities
Flange Style:
Cover type first flange
Waveguide Center To Center Distance:
18.000 inches
Waveguide Height:
17.530 inches
Flexibility:
Rigid single tubing segment
Material:
Copper alloy all tubing segment and flange
Precious Material And Location:
Internal tubing segment surfaces and flange surfaces silver
Precious Material:
Silver
Surface Treatment:
Chromate zinc single tubing segment outside surfaces and enamel single tubing segment outside surfaces
Style Designator:
Double bend type
Thread Series Designator:
Unc second flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli