NSN 5985-00-452-2228

Variable Attenuator - Page 1 of 2

Application Design:

Cylindrical w/side terminals

Audio

Body Style:



View Online at https://aerobasegroup.com/nsn/5985-00-452-2228

Overall Length:
Between 2.841 inches and 2.903 inches
Body Diameter:
2.250 inches
Shaft Diameter:
Between 0.248 inches and 0.249 inches
Bushing Length:
Between 0.781 inches and 0.843 inches
Shaft Length:
Between 0.407 inches and 0.469 inches
Body Length:
2.060 inches
Schematic Diagram Designator:
"t"
Power Rating:
600.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Attenuation Variation Method: Stepped
Stepped
Stepped Step Position Quantity:
Stepped Step Position Quantity: 20
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels:
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity:
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range:
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Overall Attenuation Accuracy In Decibels:
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Overall Attenuation Accuracy In Decibels: -0.20/+0.20
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Overall Attenuation Accuracy In Decibels: -0.20/+0.20 Mounting Thread Quantity:
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Overall Attenuation Accuracy In Decibels: -0.20/+0.20 Mounting Thread Quantity: 32 per inch
Stepped Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Overall Attenuation Accuracy In Decibels: -0.20/+0.20 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Step Position Quantity: 20 Attenuation Per Step In Decibels: 1.0 Mounting Facility Type And Quantity: 1 threaded bushing Frequency Range: Between 0.000 kilohertz and 20.000 kilohertz Overall Attenuation Accuracy In Decibels: -0.20/+0.20 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft

NSN 5985-00-452-2228

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter: 0.375 inches Impedance Rating In Ohms: 600.0 input-output Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A223a0