NSN 5985-00-452-2228

Variable Attenuator - Page 1 of 2

Application Design:

Cylindrical w/side terminals

Audio

Body Style:

Overall Length:

View Online at https://aerobasegroup.com/nsn/5985-00-452-2228



Between 2.841 inches and 2.903 inches **Body Diameter:** 2.250 inches Shaft Diameter: Between 0.248 inches and 0.249 inches **Bushing Length:** Between 0.781 inches and 0.843 inches Shaft Length: Between 0.407 inches and 0.469 inches **Body Length:** 2.060 inches Schematic Diagram Designator: "t" **Power Rating:** 600.0 milliwatts average Mounting Facility Screw Thread Series Designator: Unef **Overall Attenuation Range In Decibels:** +0.0/+20.0 **Attenuation Variation Method:** Stepped **Step Position Quantity:** 20 **Attenuation Per Step In Decibels:** 1.0 Mounting Facility Type And Quantity: 1 threaded bushing **Frequency Range:** Between 0.000 kilohertz and 20.000 kilohertz **Overall Attenuation Accuracy In Decibels:** -0.20/+0.20 **Mounting Thread Quantity:** 32 per inch Adjustment Device Type And Quantity: 1 shaft Shaft Type: Round

NSN 5985-00-452-2228

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.375 inches

Impedance Rating In Ohms:

600.0 input-output

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0