## NSN 5985-00-456-0240

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-456-0240 **Application Design:** Transmission line **Body Material: Brass Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Cadmium plated **Overall Length:** 3.750 inches **Overall Diameter:** 1.688 inches **Operating Tempurature Range:** -55.0 to 85.0 degrees celsius **Voltage Standing Wave Ratio:** 1.00 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Power Rating:** 1.0 watts average and 500.0 watts average **Rf Signal Attenuation In Decibels:** 10.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0 to 8.5 gigahertz **Attenuation Accuracy Reference Frequency:** 

8.5 gigahertz **Attenuation Accuracy In Decibels:** -0.30 to 0.30 **Frequency Sensitivity Attenuation In Decibels: Temperature Sensitivity Attenuation In Decibels:** 0.0001 **Connection Type Per Function:** Male input-output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 8.500 gigahertz

## NSN 5985-00-456-0240

Fixed Attenuator - Page 2 of 2



|  | Life: |
|--|-------|
|  |       |
|  |       |

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000