

View Online at <https://aerobasegroup.com/nsn/5985-00-457-0709>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches all flanges and 0.624 inches all flanges

Flange Inside Height:

0.309 inches all flanges and 0.313 inches all flanges

Flange Outside Width:

1.297 inches all flanges and 1.327 inches all flanges

Flange Outside Height:

1.297 inches all flanges and 1.327 inches all flanges

Flange Inside Diameter:

0.985 inches all flanges and 1.015 inches all flanges

Flange Depth:

0.360 inches all flanges and 0.390 inches all flanges

Thread Qty Per Inch (tpi):

32 all flanges all connection facilities

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.620 inches and 0.625 inches

Waveguide Inside Height:

Between 0.309 inches and 0.314 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Waveguide Longer Offset Distance:

1.843 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Offset Distance:

1.359 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all tubing segment and flange

Precious Material And Location:

External surfaces silver

Precious Material:

Silver

Surface Treatment:

Enamel baked single tubing segment outside surfaces and silver single tubing segment outside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc all flanges all connection facilities

Fsc Application Data:

Antennas, waveguides and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0