## NSN 5985-00-457-0784

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-457-0784

**Application Design:** Printed circuit board **Body Material: Brass Body Style:** Cylindrical w/side terminals **Overall Length:** 2.781 inches First Flat Length: 0.312 inches **Body Diameter:** 1.875 inches **Shaft Diameter:** Between 0.249 inches and 0.251 inches **Body Length:** 2.000 inches **Operating Tempurature Range:** +10.0/+65.0 degrees celsius **End Application:** Video integrating group an/gla-8 **Power Rating:** 0.6 watts average **Attenuation Variation Method:** Stepped **Step Position Quantity:** 30 **Attenuation Per Step In Decibels: Mounting Facility Type And Quantity:** 1 bushing **Adjustment Device Type And Quantity:** 1 shaft **Shaft Type:** Round, flatted Impedance Rating In Ohms: 10000.0 input-output **Special Features:** Contacts are solid silver alloy; includes aluminum dial with black aluminite finish **Precious Material And Location:** Contacts silver

**Precious Material:** 

Silver

## NSN 5985-00-457-0784

Variable Attenuator - Page 2 of 2



## **Terminal Type And Quantity:**

6 tab, solder lug

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A223a0