## NSN 5985-00-458-6185

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-458-6185 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 2.688 inches **Overall Diameter:** 0.830 inches **Voltage Standing Wave Ratio:** Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 2.0 watts average **Rf Signal Attenuation In Decibels:** 1.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+12.4 megahertz **Attenuation Accuracy Reference Frequency:** 12.4 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Female output and male input **Unpackaged Unit Weight:** 2.400 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range: Between 0.000 hertz

Between 0.000 hertz and 12.400 gigahertz

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

## NSN 5985-00-458-6185

Fixed Attenuator - Page 2 of 2



	<b>L</b> -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000