

View Online at <https://aerobasegroup.com/nsn/5985-00-459-0281>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

1

Flange Inside Width:

1.003 inches single flange

Flange Inside Height:

0.503 inches single flange

Flange Outside Width:

1.610 inches single flange and 1.640 inches single flange

Flange Outside Height:

1.610 inches single flange and 1.640 inches single flange

Flange Depth:

0.423 inches single flange and 0.453 inches single flange

Flange Connecting Hole Diameter:

0.169 inches single flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Adapter Length:

Between 1.266 inches and 1.296 inches

Adapter Height:

Between 1.610 inches and 1.640 inches

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole single flange all connection facilities

Flange Style:

Cover type single flange

Adapterheight:

2.480 inches

Adapterwidth:

Between 1.610 inches and 1.640 inches

Special Features:

8.2 to 12.4 ghz; temperature range minus 54.0 to plus 55.0 degrees c; connector outer conductor stainless steel, passivated; center conductor gold plated

Material:

Aluminum alloy all tubing segment and flange

Precious Material And Location:

Center conductor surfaces gold

Precious Material:

Gold

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces

Style Designator:

Waveguide to coaxial

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0