NSN 5985-00-460-9673

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-460-9673

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 all bends h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches first flange and 0.904 inches first flange

Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

Flange Depth:

0.423 inches first flange and 0.453 inches first flange

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Waveguide Length:

3.000 inches

NSN 5985-00-460-9673 Waveguide Assembly - Page 2 of 2



Waveguide Center To Center Distance:
2.350 inches
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy all tubing segment
Surface Treatment:
Enamel all tubing segment and flange outside surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0