

View Online at <https://aerobasegroup.com/nsn/5985-00-460-9998>

Body Style:

Rectangular

Overall Length:

2.480 inches

Overall Height:

1.230 inches

Overall Width:

2.120 inches

Frequency Rating:

2.0 gigahertz and 10.4 gigahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.147 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.090 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.545 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

1.780 inches single mounting facility pattern

Operating Temperature Range:

-30.0/+110.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

50.0 watts average single

Minimum Crosstalk Rating In Decibels:

50.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

50.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Rf Maximum Voltage Rating:

1.0 kilovolts rms

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Isosceles triangle single mounting facility pattern

Material:

Metal body

Terminal Type And Quantity:

2 turret and 4 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0