

View Online at <https://aerobasegroup.com/nsn/5985-00-465-7495>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches first flange and 0.904 inches first flange

Flange Inside Height:

0.396 inches first flange and 0.404 inches first flange

Flange Outside Width:

1.610 inches first flange and 1.640 inches first flange

Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

Flange Depth:

0.423 inches first flange and 0.453 inches first flange

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Waveguide Length:

4.007 inches

Waveguide Center To Center Distance:

1.100 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy first flange

Surface Treatment:

Enamel all tubing segment and flange outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0