

View Online at <https://aerobasegroup.com/nsn/5985-00-465-9226>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.362 inches second flange and 0.364 inches second flange

**Flange Inside Height:**

0.222 inches second flange and 0.224 inches second flange

**Flange Outside Width:**

0.765 inches first flange and 0.765 inches first flange

**Flange Outside Height:**

0.735 inches second flange and 0.765 inches second flange

**Flange Inside Diameter:**

0.485 inches first flange and 0.515 inches first flange

**Flange Depth:**

0.195 inches first flange and 0.225 inches first flange

**Flange Connecting Hole Diameter:**

0.116 inches second flange all connection facilities and 0.118 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.30

**Insertion Loss In Decibels:**

0.50

**Thready Qty Per Inch (tpi):**

40 first flange all connection facilities

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.358 inches and 0.362 inches

**Thread Size:**

0.112 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 0.2785 inches and 0.2815 inches

**Waveguide Inside Height:**

Between 0.1385 inches and 0.1415 inches

**Waveguide Outside Height:**

Between 0.218 inches and 0.222 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Length:**

2.911 feet

**Waveguide Center To Center Distance:**

4.000 inches

**Special Features:**

Assembly c/o four waveguide sections and two rotary joints, each section connected by a vg-599/u and a ug-600/u waveguide flange

**Flexibility:**

Rigid single tubing segment

**Material:**

Copper alloy all tubing segment and flange

**Surface Treatment:**

Any acceptable all tubing segment and flange outside surfaces

**Style Designator:**

Offset bend type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Antennas, waveguides, ans related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0