NSN 5985-00-469-5221

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-469-5221

Application Decision
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.910 inches
Overall Height:
2.030 inches
Overall Width:
2.345 inches
Scale Linearity:
Linear
Scale Division Quantity:
12
Operating Tempurature Range:
-0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.1
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
12
Attenuation Per Step In Decibels:
0.0 and 1.0 and 2.0 and 3.0 and 4.0 and 5.0 and 6.0 and 7.0 and 8.0 and 9.0 and 10.0
Mounting Facility Type And Quantity:
2 connector
Frequency Range:
Between 0.000 megahertz and 500.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.10/+0.10
Adjustment Device Type And Quantity:
1 knob
Impedance Rating In Ohms:
Impedance Rating In Ohms:

50.0 input-output

NSN 5985-00-469-5221

Variable Attenuator - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0