## NSN 5985-00-470-0148

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-470-0148 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Passivated **Overall Length:** 2.680 inches **Overall Diameter:** 0.810 inches **Voltage Standing Wave Ratio:** 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation: Power Rating:** 5.0 watts average and 1.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 60.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz **Attenuation Accuracy In Decibels:** -1.00/+1.00 **Unpackaged Unit Weight:** 0.100 kilograms **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 12.400 gigahertz **Precious Material And Location:** Contact sufaces gold **Precious Material:** Gold

Shelf Life:

N/a

## NSN 5985-00-470-0148

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000