## NSN 5985-00-471-9355

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-471-9355

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**End Application:** 

Radar set an/tps-32

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.840 inches all flanges

Flange Outside Width:

4.500 inches all flanges

Flange Outside Height:

3.625 inches all flanges

Flange Depth:

0.875 inches all flanges

**Voltage Standing Wave Ratio:** 

1.08

**Insertion Loss In Decibels:** 

0.06

**Maximum Operating Pressure:** 

35.0 pounds per square inch gage

**Waveguide Outside Width:** 

Between 2.994 inches and 3.006 inches

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

**Waveguide Inside Height:** 

Between 1.334 inches and 1.346 inches

**Waveguide Outside Height:** 

Between 1.494 inches and 1.506 inches

Flange Style:

Contact type all flanges

Waveguide Length:

Between 40.310 inches and 41.310 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber single tubing jacket

**Precious Material And Location:** 

Internal surfaces gold

**Precious Material:** 

Gold

## NSN 5985-00-471-9355

Waveguide Assembly - Page 2 of 2



_	•	_			
CIT	face	Iro	ot m	Δn	•

Chromate all flange outside surfaces and paint all flange outside surfaces

**Style Designator:** 

Straight type

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0