NSN 5985-00-472-3405

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-472-3405

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
6.080 inches
Bolt Circle Diameter:
2.120 inches
Overall Height:
2.120 inches
Overall Width:
2.240 inches
Operating Tempurature Range:
-40.0/+55.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Osm
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.7
Overall Attenuation Range In Decibels:
+0.0/+50.0
Attenuation Accuracy Reference Frequency:
9.20 gigahertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 9.150 gigahertz and 9.250 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.02/+0.02
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position circular
Mounting Facility Screw Thread Diameter:

0.138 inches

NSN 5985-00-472-3405

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms	lmp	edance	Rating	In	Ohms
--------------------------	-----	--------	--------	----	-------------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0