## NSN 5985-00-475-4234

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-00-475-4234

Brass
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Anodized
Overall Length:
6.300 inches
Overall Diameter:
1.000 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
15.0 watts average
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Unpackaged Unit Weight:
5.700 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment

## NSN 5985-00-475-4234

Fixed Attenuator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000