# NSN 5985-00-476-6135

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-476-6135

# **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

Bend Angle In Deg:

45.0 single bend e-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.834 inches first flange and 2.846 inches first flange

Flange Inside Height:

1.334 inches first flange and 1.346 inches first flange

Flange Outside Diameter:

5.298 inches first flange and 5.328 inches first flange

Flange Depth:

1.235 inches first flange and 1.265 inches first flange

**Maximum Operating Pressure:** 

5.0 pounds per square inch gage

**Waveguide Outside Width:** 

Between 2.994 inches and 3.006 inches

**Thread Size:** 

0.250 inches first flange all connection facilities

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

**Waveguide Inside Height:** 

Between 1.334 inches and 1.346 inches

**Waveguide Outside Height:** 

Between 1.494 inches and 1.506 inches

**Waveguide Longer Offset Distance:** 

1.479 feet

Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

Flange Style:

Cover type second flange

**Waveguide Offset Distance:** 

2.250 inches

Flexibility:

Rigid single tubing segment

# NSN 5985-00-476-6135

Waveguide Assembly - Page 2 of 2



			-
RΛ	late	ria	
IV	ale	:110	ı .

Aluminum all tubing segment and flange

# **Surface Treatment:**

Anodize single tubing segment outside surfaces

# **Style Designator:**

Bend type

# **Thread Series Designator:**

Unc first flange all connection facilities

# **Fsc Application Data:**

Antennas, waveguides, and related equipment

# Shelf Life:

N/a

# **Unit Of Measure:**

#### **Demilitarization:**

Yes - demil/mli

# Fiig:

A073a0