

View Online at <https://aerobasegroup.com/nsn/5985-00-476-8271>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

7.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches

Overall Height:

2.250 inches

Overall Width:

2.750 inches

Mounting Slot Width:

0.156 inches

Mounting Slot Length:

0.250 inches

Voltage Standing Wave Ratio:

1.15

Coaxial Connector Series Designation:

C

Power Rating:

500.0 milliwatts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.0

Overall Attenuation Range In Decibels:

+0.0/+20.0

Attenuation Accuracy Reference Frequency:

70.0 megahertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

7

Attenuation Per Step In Decibels:

0.5 and 1.0 and 2.0 and 3.0 and 6.0 and 10.0 and 20.0

Mounting Facility Type And Quantity:

4 slot

Frequency Range:

Between 50.000 megahertz and 70.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.10/+0.60

Segment Attenuation Range In Decibels:

+0.50/+3.00 and +3.00/+6.00 and +6.00/+10.00 and +10.00/+20.00

Segment Attenuation Accuracy In Decibels:

-0.10/+0.10 and -0.20/+0.20 and -0.30/+0.30 and -0.60/+0.60

Adjustment Device Type And Quantity:

9 lever

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0