NSN 5985-00-477-1208

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-477-1208

Application Design:

Audio

Body Style:

Cylindrical w/side terminals

Overall Length:

3.401 inches

Overall Width:

1.453 inches

Body Diameter:

1.156 inches

Scale Linearity:

Linear

Shaft Diameter:

0.125 inches

Bushing Length:

0.375 inches

Shaft Length:

1.120 inches

Body Length:

2.125 inches

Schematic Diagram Designator:

Bridged "t"

Operating Tempurature Range:

-55.0/+120.0 degrees celsius

Power Rating:

5.0 watts average

Mounting Facility Screw Thread Series Designator:

Unef

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.228

Overall Attenuation Range In Decibels:

+34.0/+43.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

1 threaded bushing

Frequency Range:

Between 0.000 gigahertz and 4.500 gigahertz

Overall Attenuation Accuracy In Decibels:

-1.00/+1.00

Mounting Thread Quantity:

32 per inch

NSN 5985-00-477-1208

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity:

2 shaft

Shaft Type:

Round, slotted

Mounting Facility Screw Thread Diameter:

0.375 inches

Impedance Rating In Ohms:

1000.0 input and 150.0 output

Special Features:

Dual concentric shaft and spst rotary switch

Test Data Document:

49675-8768316 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0