NSN 5985-00-477-1209

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-477-1209

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
4.146 inches
Overall Width:
1.453 inches
Body Diameter:
1.156 inches
Scale Linearity:
Linear
Shaft Diameter:
0.125 inches
Bushing Length:
0.375 inches
Shaft Length:
2.880 inches
Body Length:
1.266 inches
Schematic Diagram Designator:
Bridged "t"
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Power Rating:
5.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.228
Overall Attenuation Range In Decibels:
+34.0/+43.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 0.000 gigahertz and 4.500 gigahertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:

32 per inch

NSN 5985-00-477-1209

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity: 1 shaft Shaft Type: Round, slotted Mounting Facility Screw Thread Diameter: 0.375 inches Impedance Rating In Ohms: 150.0 input-output Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: -- Demilitarization: No

Fiig: A223a0