## NSN 5985-00-480-1712

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-480-1712

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
Between 2.210 inches and 2.250 inches
Overall Diameter:
0.570 inches
Operating Tempurature Range:
-55.0/+120.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
2.0 watts average and 3.0 kilowatts peak
Rf Signal Attenuation In Decibels:
40.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+5.0 gigahertz
Attenuation Accuracy Reference Frequency:
5.0 gigahertz
Attenuation Accuracy In Decibels:
-1.50/+1.50
Frequency Sensitivity Attenuation In Decibels:
1.50
Connection Type Per Function:
Male input and female output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 5.000 gigahertz

## NSN 5985-00-480-1712

Fixed Attenuator - Page 2 of 2



**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A20000